Review Paper on Aluminium Honeycomb Panel for Automotive Front Bumper

Pravin Bhame¹, Atul Patil^{2,} Ajinkya Pawar³

¹ Be Scholar, Department Of Mechanical Engineering, Dypsoe, Pune, Maharashtra, India. ² Asst. Professor, Department Of Mechanical Engineering, Jspm, Ntc, Pune, Maharashtra, India. ³ asst. Professor, Department Of Mechanical Engineering, Jspm, Rscoe, Pune, Maharashtra, India

Abstract: As One Of The Key Components Of Car, The Frontal Bumper System Plays An Important Role In The Low Speed Impact. Frontal Bumper System Protects The Principal Parts Of The Car At Low Speed Impact. In The Majority Of Crashes, The Pedestrian's Side Is Impacted By The Front Of The Car. Metal Honeycomb Are Widely Applied As Core Of Sandwich Structures Of Energy Absorbers Due To Their Excellent Mechanical And Energy Absorption Properties. The Aim Of The Paper Is To Study The Energy Absorption Capacity And Behavior Of The Aluminum Honeycomb Sandwich Panels In Low Speed Impact Of The Vehicles. The Result Of The Paper Is To Help Designer And Researcher In Performing Functional Analysis Of The Front Bumper System Of Cars.

Keywords: Aluminium, Energy Absorbers, Honeycomb Sandwich Panels, Low Speed Impact, Pedestrian.

I. Introduction

Bumpers Are Used On Automobile For Absorbing Shock And Impact From Collisions, Thereby Decreasing Injury To Pedestrian And Damage To Property, Including The Vehicle. Automotive Bumpers Typically Include An Impact Or Reinforcement Beam, Energy Absorbers Surrounding The Beam And A Fascia Surrounding The Energy The Energy Absorber. The Beam, Usually Constructed Of High Strength Steel Or Aluminium, Is Attached To The Vehicle Frame. The Energy Absorber Is Typically A Foam Material Although Hydraulic Or Gas Piston And Cylinder Assemblies Have Been Used. The Third Main Component, The Fascia, Is The Visible Exterior Of The Bumper Assembly, And Is Typically Made Of Plastic. Of The Three Main Bumper System Components, The One Most Relevant To The Present Invention Is The Energy Absorber. For Design And Construction Of Lightweight Transportation Systems Such As Satellites, Aircrafts, High Speed Trains And Racing Cars, Structural Weight Saving Is One Of The Major Considerations. To Meet These Requirements Aluminium Honeycomb Sandwich Construction Has Been Recognized As A Promising Concept.

II. Literature Review

Ines Ivanez Et Al. [1] Performed The Experimental Compressive Tests And Numerical Model To Determine The Crush Behavior And The Energy Absorption Capability Of An Aluminium Honeycomb Core By Varying The Cell Size, Cell Wall Thickness And Material Properties. Conclusion Is That The Energy Absorption Capacity Increases With Increase In Cell Wall Thickness And Energy Absorption Capacity Decreases With Increase In Cell Size.

Guangyong Sun Et Al. [2] Performed Three Point Bending (Tpb) And In Panel Compression (Ipc) Tests On Aluminium Honeycomb Sandwich Panel With Four Different Parameters Such As Thickness Of Face Sheet, Hexagonal Cell Size, Foil Thickness And Height Of Honeycomb Core To Investigate Crushing And Energy Absorbing

G Tiwari Et Al. [3] Carried Out An Experimental And Numerical Simulation On Aluminium Honeycomb Structure By Varying Cell Wall Thickness And Node Length, Keeping The Cell Size Constant To Determine The Axial Compression Behavior. Experiments Were Conducted On Compressive Testing Machine And Numerical Simulations Were Performed On Ls-Dyna.

Amit Chege Et Al. [4] Examined The Energy Absorption Capacity Of Car Bumper By Using Different Materials Such As Foam, Honeycomb, Double Cylinder Model, Double Cylinder Model Filled With Foam And Double Half Cylinder Model. The Results Show That The Two Double Half Cylinder Has The Better Energy Absorption Than Others.

P Satya Lakshmi Et Al. [5] Analyzed An Automobile Bumper Using Ansys 15.0 With Steel, Composite Steel And Honeycomb Hybrid Structure. It Is Observed That The Honeycomb Hybrid Structure Bumper Has Less Deformation Compared To Other Two Materials.

1st National Conference On Recent Innovations in Mechanical Engineering (NCRIME-2018

Arun Basil Jecob Et Al. [6] Performed Individual Crash Test Analysis Of Car Bumper Made Up Of Steel Honeycomb Structure And Aluminium Foam Using Ls-Dyna. Both The Materials Structure Shows The Better Impact Absorption Capacity Than Current Steel Bumper Of The Car.

V Siva Kumar Et Al. [7] Has Done Impact Analysis Of A Car Bumper Made Up From Different Materials With Different Loads Using Ansys 14.5. In Metals, Stainless Steel Is Suitable Materials And In Plastic Thermoplastic Olefin Is Better Material For Car Bumper.

R Hedayati Et Al. [8] Studied The Mechanical Properties Of Octagonal Honeycomb Structure Made Up From Polylactic Acid (Pla) By Using Analytical, Numerical And Experimental Approaches. All The Results Are Compared With Honeycomb Structures Having Square, Triangular, Hexagonal, Mixed, Diamond And Kamoge Unit Cell Shapes.

Dr. S. Srinivasa Rao Et Al. [9] Has Done The Analysis On Bumper Beam Made From Steel By Using Ansys 15.0 At Low Speed. Thickness Of Bumper Beam Is Varied During Analysis And Concluded That The As Thickness Increases, Stress And Deflection In Bumper Beam Is Decreases But Weight And Rigidity Also Increases. The S2 Glass Epoxy Is Proposed That Could Replace The Steel Based On Strength And Weight Criteria.

Pandey Alok S Et Al. [10] Studied The Car Bumper With Different Materials Such As Steel, Carbon Fiber Reinforced Polymer (Cfrp), Aluminium Honeycomb Sandwich Panel And Metal Foam. They Found That The Aluminium Honeycomb Have High Energy Absorbing Capacity And Low Cost And Weight. It Is Best Suited For Car Bumpers.

S A Abdul Sukkur Et Al. [11] Performed Static Analysis To Obtain The Response Of The Hexagonal Honeycomb Sandwich Made Up Of Copper Core And Stainless Steel Panel Faces By Varying Three Different Loads For Three Different Core Heights. It Is Found That The Gradient Of The Deflection Curve Is High For Lower Core Height And Stress Is Low For Higher Core Height.

Amey Gongle Et Al. [12] Has Done Analysis Of Hexagonal Honeycomb Structure Made Up From Aluminium Alloy By Using Ansys By Varying Cell Size And Keeping Sheet Thickness And Core Height Constant. Natural Frequency Of Honeycomb Structure Is Increases With Increase In Cell Size.

C Ramesh Kannan Et Al. [13] Studied Different Shapes For The Crush Can And Cuboid Seems To Be Suitable And Suggested That The Aluminium Is The Best Material For Crush Can. The Honeycomb Structure Crush Can Absorb More Energy Than The Plain Crush Can.

Praveen Kumar A. Et Al. [14] Has Done Analysis On Front Bumper Beam Of Tata 207 By Using Different Materials Like Steel, Carbon Fiber, Foam And Honeycomb Structure Using Ansys. The Result Is That The Honeycomb Structure Absorbs More Energy And Ensures Pedestrian Safety.

Xiong Zhang Et Al. [15] Studied The Crush Strength Of Aluminium Honeycomb, Experimentally And Numerically By Varying The Cell Numbers And Central Angles. Honeycomb With Different Central Angles Has No Significant Difference In Crush Strength But Has Great Influence In Crush Strength Due To Different Number Of Cells.

M Giglio Et Al. [16] Has Studied An Experimental-Numerical Methodology For The Investigation Of Three Point Bending Test (Tpbt) On Sandwich Panel Made With Thin Aluminium Skin And Nomex Honeycomb Core. Numerical Fe Reference Results Are In Good Accordance With The Experimental Results.

Ramesh S Sharma Et Al. [17] Has Done Quasi-Static Test And Impact Test On The Hexagonal Honeycomb Cell By Varying Its Height And Keeping All Other Dimensions Constant. Variation In Height Of The Honeycomb Structure Doesn't Show Any Significant Change In Energy Absorbing Capacity Of It. Top Face Absorbs More Energy Than The Core.

Mary Et Al. [18] Constructed The Bumper Beam Energy Absorber With Two Different Sized Cell Layers To Absorb More Energy And Introduced Reinforcing Material Between These Layers To Increase The Strength Of The Energy Absorber. Also Examined Extrusion Process For Manufacturing Open Cell Network.

A Masoumi Et Al. [19] Investigated Head Injury Criteria (Hic) Value By New Developed Finite Element Model By Changing The Car Bonnet Material As Steel, Aluminium And Composite At Eight Different Locations. Aluminium Has The Lowest Hic Value And Highest Displacement Than Steel.

Rikard Fredriksson Et Al. [20] Studied The Levels Of Injury Severity Of Pedestrian In Car Accidents At Different Speeds. They Concluded That The Most Commonly Injured Body Region Was Leg. At Higher Speed Head And Chest Were Dominating Body Region.

Wenhao Mu Et Al. [21] Analyzed Frontal Bumper System Of Car For Pedestrian Protection And Low Speed Impact. The Optimization Design Of Bumper For Low Speed Impact And Lower Leg Impact Was Carried Out And The Optimal Values Of Design Variables Were Obtained.

Yi-Ming Jen Et Al. [22] Determined The Bending Fatigue Strength Of Aluminium Honeycomb Sandwich Beam By Varying The Thickness Of Face Sheet And Found That No Apparent Relationship Exists Between The Face Sheet Thickness And The Fatigue Life Of Specimen.

References

- [1]. Ines Ivañez, Lorena M. Fernandez-Cañadas, Sonia Sanchez-Saez, Compressive Deformation And Energy-Absorption Capability Of Aluminium Honeycomb Core, Composite Structures (2017).
- [2]. Guangyong Sun, Xintao Huo, Dongdong Chen, Qing Li, Experimental And Numerical Study On Honeycomb Sandwich Panels Under Bending And In-Panel Compression, Materials And Design 133 (2017) 154–168.
- [3]. G. Tiwari, T. Thomas, R.P. Khandelwal, Influence Of Reinforcement In The Honeycomb Structures Under Axial Compressive Load, Thin-Walled Structures (June 2017) 0263-8231.
- [4]. Amit Chege, Kshitij, Abhishek Kale, Mohammad Rafiq B Agrewale, Dr. K.C.Vora, *Design And Development Of Impact Energy Absorbing Bumper*, International Journal Of Scientific And Engineering Research, Issn: 2229-5518, *Volume 8, Issue 3*, March 2017.
- [5]. P. Satya Lakshmi, V. Hari Shankar, Collision Analysis Of An Automobile Bumper Using Fea, International Journal Of Scientific And Research Publication, Issn 2250-3153, Volume 6, Issue 11, November 2016.
- [6]. Arun Basil Jecob, Arunkumar O. N, Improving The Crashworthiness Of An Automobile Bumper, Iosr Journal Of Mechanical And Civil Engineering, E-Issn: 278-1684 (2016) Pp 67-79.
- [7]. V.Siva Kumar, S.Timothy, M.Naga Kiran, Modeling & Impact Analysis Of A Car Bumper
- [8]. With Different Loads On Different Materials, International Journal Of Innovative Research In Science, Engineering And Technology, Issn (Online): 2319-8753, Vol. 5, Issue 11, November 2016.
- [9]. R. Hedayati, M. Sadighi, M. Mohammadi-Aghdam, A.A. Zadpoor, *Mechanical Properties Of Additively Manufactured Octagonal* Honeycombs, Materials Science And Engineering C 69 (2016) 1307–1317.
- [10]. Dr. S.Srinivasa Rao, K.Viswatej, Dr. S. Adinarayana, Design And Sensitivities Analysis On Automotive Bumper Beam Subjected To Low Velocity Impact, International Journal Of Engineering Trends And Technology (Ijett), Issn: 2231-5381, Volume 37 Number 2-July 2016.
- [11]. Pandey Alok S, Patil Nirav A, Nikumbh Pankaj S., Energy Absorbing Bumpers And It's Comparative Study, International Journal Of Innovative Research In Science And Engineering, Issn:2454-9665, Volume 2, Issue 3, March 2016.
- [12]. S. A. Abdul Sukkur, P. Palanisamy, K. R. Vijayakumar, Experimental Investigations And Finite Element Analysis Of Composite Sandwich Structures With Honeycomb Core – Evaluation For Strength And Quality, Carbon – Sci. Tech. 8/1(2016)63-73.
- [13]. Amey Gongle, Prateek Gaikwad, Modal Analysis Of Honeycomb Sandwich Panel By Varying Cell Size.
- [14]. C. Ramesh Kannan, P. Padmanabhan, G. Rajkumar, Optimization Of Bumper Design By Using Crash Test, International Journal Of Engineering Research & Technology (Ijert), Issn: 2278-0181, Vol. 3, Issue 11, November-2014.
- [15]. Praveen Kumar.A, Sameer Belagali, Bhaskar, Comparative Study Of Automotive Bumper With Different Materials For Passenger And Pedestrian Safety, Iosr Journal Of Mechanical And Civil Engineering, E-Issn: 2278-1684,P-Issn: 2320-334x, Volume 11, Issue 4 Ver. Iii (Jul- Aug. 2014), Pp 60-64.
- [16]. Xiong Zhang, Hui Zhang, Zhuzhu Wen, Experimental And Numerical Studies On The Crush Resistance Of Aluminum Honeycombs With Various Cell Configurations, International Journal Of Impact Engineering 66 (2014) 48-59.
- [17]. M. Giglio, A. Gilioli, A. Manes, Numerical Investigation Of A Three Point Bending Test On Sandwich Panels With Aluminum Skins And NomexTM Honeycomb Core, Computational Materials Science 56 (2012) 69–78.
- [18]. [17] Ramesh S. Sharma, V. P. Raghupathy, Priyamvada G. M., Abhishek A. And Abhiraj M., *Investigation Of Low Velocity Impact Response Of Aluminium Honeycomb Sandwich Panels*, Arpn Journal Of Engineering And Applied Sciences, Issn 1819-6608, Vol.6, No.11, November 2011.
- [19]. Mary, Ann Bator, Bumper Energy Absorber And Method Of Fabricating And Assembling The Same, Us 2011/0101714 A1, May 5, 2011.
- [20]. A. Masoumi, Mohammad Hassan Shojaeefard, Amir Najibi, Comparison Of Steel, Aluminum And Composite Bonnet In Terms Of Pedestrian Head Impact, Safety Science 49 (2011) 1371–1380.
- [21]. Rikard Fredriksson, Erik Rosén, Anders Kullgren, Priorities Of Pedestrian Protection—A Real-Life Study Of Severe Injuries And Car Sources, Accident Analysis And Prevention 42 (2010) 1672–1681.
- [22]. Wenhao Mu, Jikuang Yang, Optimization Design Of Frontal Bumper System For Both Pedestrian Lower Leg Protection And Low Speed Impact Requirement, Doi 10.1109/Icmtma.2013.190.
- [23]. Yi-Ming Jen, Li-Yen Chang, Effect Of Thickness Of Face Sheet On The Bending Fatigue Strength Of Aluminum Honeycomb Sandwich Beams, Engineering Failure Analysis 16 (2009) 1282–1293.